



reddot design award

# HÄFELE

# FREE SPACE BY HÄFELE

## Free Space 5.15 push



- > For flaps made from wood or with aluminum frame
- > Hinge-less stay flap fitting
- > Extremely compact: modern design and Häfele engineered technology allows more space inside the cabinet
- > Highly compact: a minimal footprint provides more storage space in furniture
- > Gentle running characteristics for easy operation
- > Fast simple installation: plugs into standard 32/37 mm line holes and fastens with pre-mounted euro screw
- > Four standard colours and product options for handle-free applications
- > Door opening can be adjusted to open 90 degrees or 107 degrees with integrated stop
- > Intuitive 3D door alignment and closing adjustment
- > Additional hinges and cover caps are not required

Model	White	Light grey	Anthracite	Black
F pto	372.27.730	372.27.530	372.27.330	372.27.430
G pto	372.27.731	372.27.531	372.27.331	372.27.431
H pto	372.27.732	372.27.532	372.27.332	372.27.432

Packing: 1 set

### Supplied with

1 stay flap fitting set (1 fitting each left/right), 2 front fixing brackets with pre-mounted screws, 1 Free push catch, 1 set of installation instructions with paper drilling template for side panel

### Order reference

The model selection of the stay flap fitting for front panels without handle depends on the cabinet height and flap weight. Model selection see sample measurements table.

Please order suitable screw set 372.27.600 for aluminium frame front panels from frame width 45 mm. Please order screw-on housing for push catch separately. We recommend to use the stronger fitting model when in doubt.

- > Area of application: For heavy stay flap applications up to 15 kg (with cabinet height 600 mm)(Push-to-Open)
- > Material: Housing: Plastic, front fixing bracket and support lever: Steel
- > Finish/colour: Front fixing bracket: Nickel plated, support lever: Nickel plated or black (with black housing), housing: White, light grey, anthracite or black
- > Opening angle: 90° or 107°
- > Adjustment facility: Height, side, tilting angle, holding power release distance on push catch
- > Installation: Fitting for screw fixing with pre-mounted Euro screw, front panel fixing without tools, for sliding onto pre-mounted fixing screw



reddot design award

# HÄFELE

# FREE SPACE BY HÄFELE

## Free Space 6.15



Model	White	Light grey	Anthracite	Black
G	372.27.721	372.27.521	372.27.321	372.27.421
H	372.27.722	372.27.522	372.27.322	372.27.422

Packing: 1 set

### Supplied with

1 stay flap fitting set (1 fitting each left/right), 2 front fixing brackets with pre-mounted screws, 1 set of installation instructions with paper drilling template for side panel

### Order reference

The choice of the stay flap fitting for front panels with handle depends on the cabinet height and flap weight including handle. Model selection see sample measurements table.

Please order suitable screw set 372.27.600 for aluminum frame front panels from frame width 45 mm. We recommend to use the stronger fitting model when in doubt.

- > For flaps made from wood or with aluminum frame
- > Hinge-less stay flap fitting
- > Extremely compact: modern design and Hafele engineered technology allows more space inside the cabinet
- > Highly compact: a minimal footprint provides more storage space in furniture
- > Gentle running characteristics for easy operation
- > Fast simple installation: plugs into standard 32/37 mm line holes and fastens with pre-mounted euro screw
- > Four standard colours and product options for handle-free applications
- > Door opening can be adjusted to open 90 degrees or 107 degrees with integrated stop
- > Intuitive 3D door alignment and closing adjustment
- > Additional hinges and cover caps are not required

- > Area of application: For heavy stay flap applications up to 15 kg (with cabinet height 600 mm)
- > Material: Housing: Plastic, front fixing bracket and support lever: Steel
- > Finish/colour: Front fixing bracket: Nickel plated, support lever: Nickel plated or black (with black housing), housing: White, light grey, anthracite or black
- > Opening angle: 90° or 107°
- > Adjustment facility: Height, side, tilting angle, holding power
- > Installation: Fitting for screw fixing with pre-mounted Euro screw, front panel fixing without tools, for sliding onto pre-mounted fixing screws